



**FLEXIBLE FLAT TINNED COPPER BRAID GROUND STRAPS
 CRIMPED EYELET TERMINATIONS
 GS-15 UNINSULATED, FOR INSULATED CHANGE P/N TO GSI-15**

Add length in Inches (hole to hole) after part no.

Insulation available in Black or Green/Yellow

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
4/0	225600	2256 X 30	390	2.125	GS15-4/0
3/0	153600	1536 X 30	290	2.000	GS15-3/0
2/0	124800	1248 X 30	250	2.000	GS15-2/0
1/0	105600	1056 X 30	235	1.750	GS15-1/0
1	76800	768 X 30	180	1.625	GS15-001
2	64800	648 X 30	155	1.375	GS15-002
3	52800	528 X 30	145	1.375	GS15003
4	38400	384 X 30	120	1.000	GS15-004
5	33600	336 X 30	100	1.000	GS15-005
6	24000	240 X 30	93	0.750	GS15-006
7	20800	864 X 36	85	0.750	GS15-007
8	16800	168 X 30	75	0.625	GS15-008
9	13200	528 X 36	62	0.625	GS15-009
10	9600	384 X 30	53	0.375	GS15-010
11	7800	312 X 36	46	0.281	GS15-011
12	6000	240 X 36	40	0.250	GS15-012

Please provide hole size for lugs when placing your order.