

EXTRA FLEXIBLE, ROUND, ROPE LAY, BARE COPPER CABLE STRAPS

For use where flexible and extended flex-life is of primary consideration

Add length in Inches (hole to hole) after part number..

Insulation available in Black or Green/Yellow).

The amperage ratings shown are for non-insulated braid and provided as a guide only. These ratings will vary with service conditions, ambient temperature and proximity to other components. All dimensions are nominal.

ABLE PART NO.	AWG SIZE	CIRCULAR MIL AREA	NO & AWG OF STRAND	APPROX AMPS	NOM WIDTH	ABLE PART NO.
GS14-400	4/0	212800	8512 X 36	350	.685*	GSI-14-400
GS14-300	3/0	169575	6783 X 36	315	0.611	GSI-14-300
GS14-200	2/0	132300	5292 X 36	252	0.533	GSI-14-200
GS14-100	1/0	105350	4214 X 36	214	0.475	GSI-14-100
GS14-001	1	83300	3332 X 36	183	0.423	GSI-14-001
GS14-002	2	66150	2646 X 36	160	0.377	GSI-14-002
GS14-004	4	41650	1666 X36	114	0.299	GSI-14-004
GS14-006	6	26250	1050 X 36	80	0.210	GSI-14-006
GS14-008	8	16625	665 X 36	62	0.167	GSI-14-008
GS14-010	10	10325	416 X 36	46	0.131	GSI-14-010
GS14-012	12	6475	259 X 36	31	0.104	GSI-14-012
GS14-014	14	4200	168 X 36	25	0.084	GSI-14-014
GS14-016	16	2625	105 X 36	17	0.067	GSI-14-016
GS14-018	18	1575	63 X 36	13	0.052	GSI-14-018
GS14-020	20	1050	42 X 36	9	0.042	GSI-14-020

Please provide hole size for lugs when placing your order.